| SPECIFICATIONS | | | |
|------------------------------|---------|------|--|
| PARAMETERS | VALUES | UNIT | |
| DIRECTIVITY | OMINI | - | |
| SENSITIVTY | -40 ± 3 | dB | |
| STANDARD OPERATING VOLTAGE | 2 | Vdc | |
| MAX OPERATING VOLTAGE | 10 | Vdc | |
| CURRENT CONSUMPTION (MAX) | 0.5 | mA | |
| IMPEDANCE | 2.2 | KOhm | |
| SIGNAL TO NOISE RATIO (MIN.) | 60 | dB | |
| TERMINAL | PIN | - | |
| INTERNAL CAPACITOR | 33 | pF | |

2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL

3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

4. MICROPHONE CLOTH OVER FACE IS IP51 RATED.

WITHOUT NOTICE.

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

| ©2003, Projects | Unlimited | Inc |
|-----------------|-----------|-----|
|-----------------|-----------|-----|

| REVISION HISTORY | | | | | |
|------------------|--|-----------|----------|--|--|
| LTR | DESCRIPTION | DATE | APPROVED | | |
| - | RELEASED FROM ENGINEERING | 3/23/2006 | | | |
| Α | REVISED TO INVENTOR 3-D DRAWING TEMPLATE | 10/6/2010 | B.R. | | |
| В | REVISED DIMENSIONS | 2/14/2020 | M.V. | | |

Checked by

B.R.

Approved by

E.P.

Microphone

POM-2740P-C33-R

Date

3/23/2006 10/6/2010


Drawn Date

Sheet

1/1

Date

3/23/2006



UNLESS OTHERWISE

SPECIFIED:

DIMENSIONS ARE IN MILLIMETERS,

TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.

POM-2740P-C33-R.idw

Designed by

T.G.

SIZE

Date

3/23/2006