

SPECIFICATIONS					
PARAMETERS	VALUES	UNITS			
RATED INPUT POWER	0.5	W			
MAX INPUT POWER	1	W			
IMPEDANCE	8 ± 15%	OHM			
OUTPUT SPL @ 1W/50CM	82 ± 3	dBA			
(AT 0.8, 1.0, 1.2, 1.5 kHz)	02 1 3	UDA			
DISTORTION (MAX.)	5%	-			
RESONANT FREQUENCY	650 ± 20%	Hz			
FREQUENCY RANGE	650 ~ 15,000	Hz			
HOUSING MATERIAL	METAL	-			
CONE MATERIAL	MYLR	-			
MAGNET MATERIAL	Nd-Fe-B	-			
OPERATING TEMPERATURE	-20 ~ +60	°C			
WEIGHT	5.2	grams			


THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

REVISION HISTORY						
LTR	DESCRIPTION	DATE	APPROVED			
-	RELEASED FROM ENGINEERING	11/8/2005				
Α	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	11/6/2008	B.R.			
В	REVISED OPERATING TEMP AND DIMENSIONS	11/1/2013	M.L.			
С	REVISED MAGNET DIAMETER TO 12.9mm	5/24/2016	M.L.			
D	REVISED SPL RATING DISTANCE FROM 1M TO 50CM	8/18/2017	M.V.			







Drawn Date

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 20011/65/EU COMPLIANT.

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN MILLIMETERS.	SIZE
TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.	A3
AS03008N	1R-R.idw

Designed by	Date	Che	скеа ру	Date	Approved by	Date		Drawn Date
J.A.F.	11/8/2005 E		B.R. 11/8/2005 E.P. 11/8/2		11/8/20	005	11/6/2008	
pul.			AS03008MR-R					
	a projects unlimited co	ınc		Spea	aker		Editio	Sheet 1 / 1