
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.


■ 2005, Projects Unlimited Inc.

SPECIFICATIONS

	REVISIONS					
LTR	DESCRIPTION	DATE	APPROVED			
-	RELEASED FROM ENGINEERING	4/21/15				

PARAMETERS	VALUES	UNITS
DIRECTIVITY	Omni	_
SENSITIVITY	-38±3	dB
STANDARD OPERATING VOLTAGE	2	Vdc
MAX OPERATING VOLTAGE	10	Vdc
CURRENT CONSUMPTION (MAX)	0.5	mA
IMPEDANCE	2.2	kOhm
SIGNAL TO NOISE RATIO (MIN.)	>58	dB
TERMINAL	PIN	-
INTERNAL CAPACITOR	10 & 33	pF
OPERATING TEMPERATURE	-20~60	•c





NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2011/65/EU COMPLIANT.
- 4. THIS PART IS BACK ELECTRET.
- 5. THIS PART IS IP67 RATED.



ENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.

3541 Stop Eight Road Dayton, Ohio 45414

	APP	DATE	
	DRAWN	M.L.	3/15
' (CHECKED	M.L.	3/15
	APPROVED	B.R.	3/15

MICROPHONE DRAWING NO.

TOW-1538P-C3310-R SCALE: N.T.S. SHEET 1

TOW-1538P-C3310-R.DW