



PUIaudio



Data Sheet	AS02204CR
------------	-----------

The **AS02204CR** is designed for applications such as hand-held devices, portable devices, and devices that value compact design.

Features:


- 83dB SPL: $P_{DRIVE} = 1.0W$, distance = 0.1m
- 3.0W continuous dissipation
- 850Hz free-air resonance
- 22.0mm diameter x 6.4mm dimensions

Specifications


(Specifications measured with following conditions: ambient temperature; $15^{\circ}C \leq T_A \leq 35^{\circ}C$, relative humidity; $25\% \leq RH_A \leq 75\%$, according to standard GB/T9396-1996, unless otherwise stated. Judgement Condition: ambient temperature; $20 \pm 2^{\circ}C$; relative humidity; $63\% \leq RH_A \leq 67\%$. Product shelf life valid for 12 months.

Parameters	Values	Units
Rated Input Power	3.0	Watts
Max Input Power	3.5	Watts
Impedance	$4 \pm 15\%$	Ohms
Sensitivity (SPL) $P_{DRIVE} = 1.0W$, distance = 0.1m f = ave. 0.8kHz, 1.0kHz, 1.2kHz, 1.5kHz	83 ± 3	dB
Resonant Frequency (f_0)	$850 \pm 20\%$	Hz
Frequency Range (-10 dB)	$850 \leq f \leq 20,000$	Hz
Total Harmonic Distortion (THD) f = 1kHz, $P_{DRIVE} = 1.0W$	≤ 10	%
Frame Material	PBT + 15% GF	-
Magnet Material	NdFeB	-
Diaphragm Material	Cloth + Aluminum	-
Weight	4.8	gm
Buzz, Rattle, etc.	Not audible with $P_{DRIVE} = 3.0W$, sine wave, $680 \leq f \leq 20,000$	-
Polarity	Applying positive dc current to "+" terminal moves diaphragm forward	-
Operating Temperature	$-25 \leq T_O \leq 50$	$^{\circ}C$
Storage Temperature	$-25 \leq T_S \leq 60$	$^{\circ}C$
Environmental Compliances	ROHS/REACH	-


Measurement Method (measured with $P_{DRIVE} = 1.0$, distance = 0.5m)




Typical Frequency Response ($P_{DRIVE} = 1W$, distance = 0.5m)




Typical THD vs. Frequency ($P_{DRIVE} = 1W$)




Typical Impedance Response



Reliability Testing

Type of Test	Test Specifications	Judgement
High Temperature Test GB2423.2-81	96 hours at +85°C ± 2°C followed by one hour in normal room temperature	SPL shall not deviate by ±3dB. Resonant frequency shall not deviate by ±50Hz. (compared with pre-test measurement)
Low Temperature Test GB2423.1-81	96 hours at -40°C ± 2°C followed by one hour in normal room temperature	
Humidity Test GB5170.18-87	96 hours at +40°C ± 2°C with relative humidity between 90% and 95% followed by 6 hours in normal room temperature	
Temperature Cycle Testing GB5170.18-87	 <p>The diagram shows a temperature cycle starting at Room Temperature +25°C. It ramps up to +85°C in 10 seconds, holds for 1 hour, ramps down to -40°C in 10 seconds, and holds for 1 hour. This cycle repeats 4 times before returning to the start.</p>	
Vibration Test GB11606.8-89	Frequency 30±15 Hz, Amplitude 1.5 mm for 3 Hours	SPL shall not deviate by ±3dB. (compared with pre-test measurement)
Drop Test GB2423.8-81	75 cm free falling on concrete floor, 10 times.	
Load Test GB/T12060.5-2011	Speaker should not fail after applying 20Hz ~ 20kHz pink noise with HPF rated power input (RMS), 96 hours.	



Dimensions



Packaging

42pcs per tray

15 trays/630pcs master carton



Measurement & Standard Reference

Abstract from GB/T 9396-1996 and IEC 268-5:1989: methods of measurement for main characteristics of loudspeakers.

5.1 Rated sine voltage.

A sinusoidal signal voltage specified by the manufacturer which makes the speaker work continuously in the rated frequency range, without causing electrical or mechanical damage to the speaker. The continuous voltage time is 1 hour.

5.2 Rated sine power.

The rated sine power corresponding with the rated sine voltage defined by: U_s^2/R , where U_s indicates the rated sin voltage and R indicates the rated impedance of the speaker.

5.3 Rated noise power.

The rated sine power corresponding with the rated sine voltage defined by: U_n^2/R , where U_n indicates the rated sin voltage and R indicates the rated impedance of the speaker.

Specifications Revisions

Revision	Description	Date	Approved
A	Datasheet released from Engineering	3/11/2024	KH

Note:

- 1. Unless otherwise specified:
 - A. All dimensions are in millimeters.
 - B. Default tolerances are $\pm 0.5\text{mm}$ and angles are $\pm 3^\circ$, unless otherwise specified.
- 2. Specifications subject to change or withdrawal without notice.